

Art. nr.: 60000099

---

# Montage Handleiding







## Installation Instructions





1. Silo / Steel silo
2. Silobekleding / Silo liner
3. Doorvoer / Outlet
4. Anti-alg spanzeil / Anti-algae tension cover
5. Silofloat<sup>®</sup> drijfzeil / Silofloat<sup>®</sup> floating cover

# I Silo / Steel Silo






## Ia Betonvloer / Concrete floor





Zie ook pag. 4 / see also page 4



# Ib Betontegels / Concrete slabs




Zie ook pag. 4 / see also page 4




# Bodemvilt / Bottom protection sheet

## 1c Silo / Steel Silo $\leq 14,0$ m.



## 2c Silo / Steel Silo $> 14,0$ m.





# 2 Silobekleding / Silo liner



## 2a Silo / Steel Silo $\leq \text{Ø}14,0$ m

**Attentie: PVC Liners monteren bij  $T > +5^{\circ}\text{C}$  (folie- en buitentemperatuur!)**





**Attention: PVC Liner installation at  $T > +5^{\circ}\text{C} / 41^{\circ}\text{F}$  (lining and ambient temperature!)**




Genap b.v. rev.14 0517



## 2b Silo / Steel Silo > Ø14,0 m







## Ophanging met ring-koord / Fixation with eyelet-cord







Genap b.v. rev.14 0517

# 3 Doorvoer / Outlet

## 3a Op locatie / on site





## 3b In silobekleding / in Silo liner



# 4 Anti-alg spanzeil / Anti-algae tension cover

4a Binnen gebruik; Buiten gebruik silo ≤ Ø7,0 m / Inside use; outside use silo ≤ Ø7,0 m




# 5 Silofloat® drijfzeil / floating cover

'Lege' silo: max. 25 cm. water; 'Volle' silo: minstens tot 30 cm. onder de rand gevuld  
 'Empty' silo: max. 25 cm. water; 'Full' silo: at least 30 cm. under top edge silo




1. Buis verbinding/pipe connection



2. PVC tape; A = min. 15 cm.




3. Schuim / foam rubbers / PVC tape





Doorsnede / cross section



Buis inlaat / pipe inlet



Opening in zeil knippen / cut opening in cover



Installatie ring rondschuim / installation foam ring